









	Pro	Lite
Code model	YLHGN11-06D0WBS001	YLCGN11-06D0WB0001
Capacity	6 trays GN 1/1	6 trays GN 1/1
Pitch	70 mm	70 mm
Dimension mm (LxDxH)	510x905x850	510x905x850
Weight (kg)	83 kg	79 kg
Power	10,5 kW	7,5 kW
Voltage	380-415 V / 3 N	380-415 V / 3 N
IP protection level	IPx 4	IPx 4



Main features (Pro unit)

- $\hfill\square$ Convection, combi and steam cooking with fixed time or core probe function
- ☐ Temperature settable from 30°C to 280°C
- ACT Technology (Advanced Clima Technology) with energy conservation thanks to the automatic climate regulation**
- Manual, programmed or automatic cooking mode
- Pre uploaded YESRECIPES book divided into categories
- MYCOOKBOOK for saving programs into customizable folders
- ☐ Manual or automatic pre-heating mode settable up to 300°c
- Possibility to save up to 10 cooking phases per program
- ☐ HOLD function at the end of the cooking
- 10" multilingual Touchscreen display
- ☐ Click&Share function to save recipes with your cover images
- USB interface for HACCP data downloading
- Integrated WIFI connection configuration
- Alarms display with autodiagnosis system
- Special cycles: Delta T, Time's up for synchronized cookings, Cook&Go for simultaneous cookings, rapid cooking chamber cool-down, regeneration with core probe or fixed-time mode, proofing cycle
- $\ \square$ Manual humidity supply function
- ☐ FastSteam technology for immediate steam generation
- YesSteam technology for steam generation with high efficiency steamer**

- ☐ Programmable FCS technology (Fast Chimney System) for forced extraction of humidity
- Automatic SCS technology (Smart Chimney System) for forced extraction of humidity
- lacksquare Settable ventilation speeds (7) + pulse speed with automatic inversion of fans rotation
- 304 stainless steel cooking chamber
- Ergonomic and lightweight handle compliant with HACCP standards
- ☐ Frontal structure with screwless system
- Integrated humidity collector aisle
- Multi-point core probe with external link to the cooking chamber included
- Integrated syphon
- ☐ Adjustable feet
- Simply-removable tray holder
- ☐ Double glass door with high thermic insulation and easy inspection with safety fan stop system when the door is open
- ☐ Halogen inner lamps in the cooking chamber
- Retractable shower included**
- Automatic washing system with monocomponent YesClean (4+1 cycles)
- ☐ Automatic special cycle for limescale removal from the steamer**
- Loading detergent function
- Integrated mono product tank (YesClean)

^{**} Not available for Lite unit

		YLHGN11-06D0 WBS001	YLCGN11-06D0
	Code model	7 %	7
	Capacity	6	
quipment unit	Pro unit (full optional)	ě	
	Lite unit Classic unit		
	Convection, combi and steam cooking		
ookina tuno	Convection, combi and steam cooking with fixed time or core probe function Convection, combi and steam cooking with fixed time or core probe function (mono-point core probe optional)	•	
ooking type	Convection, combi and steam cooking with fixed time or core probe function (mono-point core probe optional) Convection, combi and steam cooking with fixed time or core probe function (multi-point core probe optional)		
	ACT technology (advanced clima technology) with energy conservation thanks to the automatic climate regulation	•	
emperature	Temperature settable from 30°c to 280°c Manual cooking mode	•	
ooking mode	Programmed cooking mode	•	
	Automatic cooking mode	•	
	Data storage for the saving programs (99) Pre uploaded YESRECIPES book divided into categories		
ecipes memory	MYCOOKBOOK for saving programs into customizable folders	•	
	Rapid display of free and in use positions		
ooking phases	5 cooking phases per program 10 cooking phases per program	•	
31	HOLD function at the end of the cooking	•	
e-heating	Manual or automatic pre-heating mode settable up to 280°c Manual or automatic pre-heating mode settable up to 300°c	•	
	Manual controls		
ven interface	Multi-function digital display		
	Multi-function digital display with Yesclima function 10"multilingual touchscreen display	•	
	Click&Share function to save recipes with your cover images	•	
ripheral devices	USB interface for data uploading and downloading (HACCP data also)	•	
	Configuration for integrated WIFI connection Possibility to modify cooking parameters during the cycle in operation	•	
difications and	Instant display of set cooking parameters	•	
play	Instant display of the set-up cooking program	•	
	Alarms display with autodiagnosis system Delta T special cooking cycle	•	
	Time's Up special cycle for synchronized cookings	•	
	Cook&Go special cycle for simultaneous cookings	•	
ecial cycles	Rapid cooking chamber cool-down special cycle Regeneration special cycle	•	
	Proofing special cycle	•	
	Special cycle time extension at the end of the cooking process Rapid cancellation of memorized recipes	•	
	Manual humidity supply function	•	
umidity and	Humidity release from 0% to 100%		
eam generation	Fast Steam technology for immediate steam generation YesSteam technology for steam generation with high-efficiency steamer		
	Manual system for forced extraction of humidity	•	
umidity extraction	Programmable FCS technology (fast chimney system) for forced extraction of humidity	•	
	Automatic SCS technology (smart chimney system) for forced extraction of humidity Mono-fan heat supply system		
eat supply	Multi-fan heat supply system		
	Special ventilation SOFT-BAKING		
ns speed	Settable ventilation speeds (3) with automatic inversion of fan rotation Settable ventilation speeds (7) with automatic inversion of fan rotation	•	
	Special ventilation pulse speed with automatic inversion of fan rotation	•	
	304 stainless steel cooking chamber	•	
oking chamber	304 stainless steel molded cooking chamber 316 stainless steel molded cooking chamber		
	304 stainless steel control panel structure	•	
	Frontal structure with screwless system Simply comprehensive page.		
	Simply-removable control panel Simply-approachable right side		
	Simply-approachable motor compartment		
	Integrated humidity collector aisle Double chimney	•	
en structure	Mono-point core probe with external link to the cooking chamber		
	Multi-point core probe with external link to the cooking chamber	•	
	Integrated syphon Adjustable feet		
	Stackable kit configuration		
	Simply removable rack holder	••	(
	Simply removable tray holder Ergonomic and lightweight handle compliant with HACCP standards	•	
or	Reversible door opening R/L (optional only at the order placement)		
hatin a	Double glass door of easy inspection with high thermic insulation	•	
nting 	Halogen inner lamps in the cooking chamber Cooling fan for components protection		
urity	Safety fanstop when the door is open	•	
	Manual external shower		
alatia a	Retractable shower Automatic washing system with monocomponent YesClean (4+1 cycles)		
shing	Loading detergent function for checking the washing system status	•	
	Integrated monoproduct tank (YesClean)	•	



General Accessories

All Line

External shower kit
YesClean detergent (box with 12 pcs 1kg each)
YesCal limescale product for steamer washing (box with 12 pcs 1kg each)
Cartridge filter mod.XL with connection head
Cartridge filter mod.XL
Connection head for cartridge filter mod.XL
Stand wheels kit
Multi-point core probe for ego, star, ego rack and ego slim ovens
Mono-point core probe for mood and taos ovens

Ho.Re.Ca. & Bakery Line

YSTG7	6 levels stand (LxDxH) 850x890x720 mm
YABGN64-5D	5 levels proofer/blast chiller unit (LxDxH) 750x730x850 mm
390200008	6 trays 600x400 rackholder (L/R)
390200001	6 trays 600x400 trayholder (L/R)
390100006	7 trays GN 1/1 rackholder (L/R)
390200002	7 trays GN 1/1 trayholder (L/R)
390200005	10 trays 600x400 rackholder (L/R)
390200003	10 trays 600x400 trayholder (L/R)
390100007	11 trays GN 1/1 rackholder (L/R)
390200004	11 trays GN 1/1 trayholder (L/R)
YSTKIT	Stackable kit
YSTSTK	Stand for stackable column (LxDxH) 850x850x282 mm
YPSTK6040-M	12 trays 600x400 mechanical ventilated proofer (LxDxH) 850x930x740 mm
YPSTK6040-D	12 trays 600x400 digital ventilated proofer (LxDxH) 850x930x740 mm
ON DEMAND	Stainless steel AISI 316 cooking chamber for ego and star 6/7 trays ovens
ON DEMAND	Stainless steel AISI 316 cooking chamber for ego and star 10/11 trays ovens
-	Reversible door opening R/L (optional only at the order placement)

Special Line

142000002	20 trays GN 1/1 trolley for ego rack
142000001	16 trays 600x400 trolley for ego rack
YSTSLIM	6 levels stand (LxDxH) 513x908x687 mm for ego slim

Trays

GN 1/1 trays for **Ho.Re.Ca.** Line

	•
220100006	Aluminum not-stick tray for 6 eggs d.53x32,5 cm
220100007	Steel granite enameled tray h.20 GN 1/1
220100009	Pizza tray d.53x32,5 cm
220100014	Aluminum not-stick perforated tray h.20 d. 53x32,5 cm
220100015	Aluminum not-stick tray h.20 d.53x32,5 cm
230100002	Chromed grill rack d.53x32,5 cm
230100005	Roast chicken tray (8 spikes) d.53x32,5 cm
230100006	Grill tray d.53x32,5 cm
220200003	Stainless steel tray h.20 d.53x32,5 cm
220200002	Stainless steel tray h.40 d.53x32,5 cm
220200004	Stainless steel perforated tray h.20 d.53x32,5 cm
220100005	Fry steel tray h.40 d.53x32,5 cm

600x400 trays for **Bakery** Line

220100001	Aluminum tray h.20 600x400
220100008	Pizza tray h.20 600x400
220100010	Aluminum perforated tray h.20 600x400
230100001	Grill rack tray 600x400