











Pro



YEOGN11M07D0WB0000
7 trays GN 1/1
70 mm
850x890x890
105 kg
18 kW
380-415 V / 3 N
IPx 4

Lite

	Pro	Lite
Code model	YEOGN11M11D0WBS000	YEOGN11M11D0WB0000
Capacity	11 trays GN 1/1	11 trays GN 1/1
Pitch	70 mm	70 mm
Dimension mm (LxDxH)	850x890x1170	850x890x1170
Weight (kg)	142 kg	142 kg
Power	24 kW	24 kW
Voltage	380-415 V / 3 N	380-415 V / 3 N
IP protection level	IPx 4	IPx 4

## Main features (Pro unit)

- $\hfill\square$  Convection, combi and steam cooking with fixed time or core probe function
- $\blacksquare$  Temperature settable from 30°C to 280°C
- ACT Technology (Advanced Clima Technology) with energy conservation thanks to the automatic climate regulation
- ☐ Manual, programmed or automatic cooking mode
- Pre uploaded YESRECIPES book divided into categories
- MYCOOKBOOK for saving programs into customizable folders
- ☐ Manual or automatic pre-heating mode settable up to 300°c
- Possibility to save up to 10 cooking phases per program
- HOLD function at the end of the cooking
- $\blacksquare$  10" multilingual Touchscreen display
- Click&Share function to save recipes with your cover images
- $\ \square$  USB interface for HACCP data downloading
- ☐ Integrated WIFI connection configuration
- $\hfill\square$  Alarms display with autodiagnosis system
- Special cycles: Delta T, Time's up for synchronized cookings, Cook&Go for simultaneous cookings, rapid cooking chamber cooldown, regeneration with core probe or fixed-time mode, proofing cycle
- ☐ Manual humidity supply function
- $\ \square$  FastSteam technology for immediate steam generation
- ☐ YesSteam technology for steam generation with high efficiency steamer
- Programmable FCS technology (Fast Chimney System) for forced extraction of humidity
- Automatic SCS technology (Smart Chimney System) for forced extraction of humidity

- ☐ Settable ventilation speeds (7) + pulse speed with automatic inversion of fans rotation
- ☐ 304 stainless steel molded cooking chamber
- Ergonomic and lightweight handle compliant with HACCP standards
- □ 304 stainless steel control panel structure
- ☐ Frontal structure with screwless system
- ☐ Simply-removable control panel
- ☐ Simply-approachable right side
- ☐ Simply approachable motor compartment
- Integrated humidity collector aisle
- Multi-point core probe with external link to the cooking chamber included
- ☐ Integrated syphon
- Adjustable feet
- Stackable kit configuration
- ☐ Simply-removable tray holder
- Reversible door opening R/L\*
- $\hfill \Box$  Double glass door with high thermic insulation and easy inspection with safety fan stop system when the door is open
- Halogen inner lamps in the cooking chamber
- ☐ Retractable shower included\*\*
- Automatic washing system with monocomponent YesClean (4+1 cycles)
- ${\color{red} {f \square}}$  Automatic special cycle for limescale removal from the steamer
- Loading detergent function
- ☐ Integrated mono product tanks (YesClean and YesCal)

<sup>\*</sup> Optional only at the order placement

		M07[	M07[	M11[	M11[
<b>20</b> 0	0_	YEOGN11M07D 0WBS000	YEOGN11M07D 0WB0000	YEOGN11M11D 0WBS000	YEOGN11M11D
9		YEOGN1	YEOGN1	YEOGN1	YEOGN1
	Code model	, 0			
quipment unit	Capacity Pro unit (full optional)	7	7	11	11
quipinent unit	Lite unit		•	•	•
	Classic unit				
	Convection, combi and steam cooking  Convection, combi and steam cooking with fixed time or core probe function	•	•	•	
Cooking type	Convection, combi and steam cooking with fixed time or core probe function (mono-point core probe optional)				
	Convection, combi and steam cooking with fixed time or core probe function (multi-point core probe optional)				
emperature	ACT technology (advanced clima technology) with energy conservation thanks to the automatic climate regulation  Temperature settable from 30°c to 280°c	•	•	•	
	Manual cooking mode	•	•	•	•
ooking mode	Programmed cooking mode	•	•	•	
	Automatic cooking mode  Data storage for the saving programs (99)				
ecipes memory	Pre uploaded YESRECIPES book divided into categories	•	•	•	•
capesmemory	MYCOOKBOOK for saving programs into customizable folders Rapid display of free and in use positions	•	•	•	•
	5 cooking phases per program				
ooking phases	10 cooking phases per program	•	•	•	•
	HOLD function at the end of the cooking  Manual or automatic pre-heating mode settable up to 280°c	•	•	•	•
re-heating	Manual or automatic pre-heating mode settable up to 300°c	•	•	•	•
	Manual controls				
oven interface	Multi-function digital display  Multi-function digital display with Yesclima function				
	10"multilingual touchscreen display	•	•	•	•
	Click&Share function to save recipes with your cover images	•	•	•	•
eripheral devices	USB interface for data uploading and downloading (HACCP data also)  Configuration for integrated WIFI connection	•		•	•
	Possibility to modify cooking parameters during the cycle in operation	•	•	•	•
Modifications and	Instant display of set cooking parameters	•	•	•	•
isplay	Instant display of the set-up cooking program  Alarms display with autodiagnosis system	•	•	•	
	Delta T special cooking cycle	•	•	•	•
	Time's Up special cycle for synchronized cookings	•	•	•	•
	Cook&Go special cycle for simultaneous cookings Rapid cooking chamber cool-down special cycle	•	•	•	
pecial cycles	Regeneration special cycle	•	•	•	•
	Proofing special cycle	•	•	•	•
	Special cycle time extension at the end of the cooking process  Rapid cancellation of memorized recipes			•	
	Manual humidity supply function	•	•	•	•
lumidity and team generation	Humidity release from 0% to 100% Fast Steam technology for immediate steam generation				
team generation	YesSteam technology for steam generation with high-efficiency steamer	•	•	•	
	Manual system for forced extraction of humidity				
lumidity extraction	Programmable FCS technology (fast chimney system) for forced extraction of humidity  Automatic SCS technology (smart chimney system) for forced extraction of humidity	•		•	
laat ayaaly	Mono-fan heat supply system	•	•		
leat supply	Multi-fan heat supply system			•	•
	Special ventilation SOFT-BAKING Settable ventilation speeds (3) with automatic inversion of fan rotation				
ans speed	Settable ventilation speeds (7) with automatic inversion of fan rotation	•	•	•	•
	Special ventilation pulse speed with automatic inversion of fan rotation	•	•	•	•
ooking chamber	304 stainless steel cooking chamber 304 stainless steel molded cooking chamber	•	•	•	•
	316 stainless steel molded cooking chamber	••	••	••	0
	304 stainless steel control panel structure	•	•	•	0
	Frontal structure with screwless system Simply-removable control panel	•	•	•	•
	Simply-approachable right side	•	•	•	•
	Simply-approachable motor compartment  Integrated humidity collector aisle	•	•	•	0
huan atriuatura	Double chimney	•	•	•	•
ven structure	Mono-point core probe with external link to the cooking chamber				
	Multi-point core probe with external link to the cooking chamber  Integrated syphon		0	•	
	Adjustable feet	•	•	•	•
	Stackable kit configuration	••	••	••	00
	Simply removable rack holder Simply removable tray holder	•	•	•	0
	Ergonomic and lightweight handle compliant with HACCP standards	•	•	•	•
oor	Reversible door opening R/L (optional only at the order placement)	••	••	••	•
ahtina	Double glass door of easy inspection with high thermic insulation  Halogen inner lamps in the cooking chamber	•	•	•	0
ghting	Cooling fan for components protection	•	•	•	0
ecurity	Safety fanstop when the door is open	•	•	•	•
	Manual external shower Retractable shower	•	••	•	•
/ashing	Automatic washing system with monocomponent YesClean (4+1 cycles)	•	•	•	•
·asimiy	Loading detergent function for checking the washing system status	•	•	•	•
	Integrated monoproduct tank (YesClean)	•	•	•	



# **General Accessories**

#### **All** Line

260700004	External shower kit
400100013	YesClean detergent (box with 12 pcs 1kg each)
400100022	YesCal limescale product for steamer washing (box with 12 pcs 1kg each)
260900001	Cartridge filter mod.XL with connection head
260900001-1	Cartridge filter mod.XL
260900001-2	Connection head for cartridge filter mod.XL
YSTW	Stand wheels kit
061200013	Multi-point core probe for ego, star, ego rack and ego slim ovens
061200007	Mono-point core probe for mood and taos ovens

#### Ho.Re.Ca. & Bakery Line

YSTG7	6 levels stand (LxDxH) 850x890x720 mm
YABGN64-5D	5 levels proofer/blast chiller unit (LxDxH) 750x730x850 mm
390200008	6 trays 600x400 rackholder (L/R)
390200001	6 trays 600x400 trayholder (L/R)
390100006	7 trays GN 1/1 rackholder (L/R)
390200002	7 trays GN 1/1 trayholder (L/R)
390200005	10 trays 600x400 rackholder (L/R)
390200003	10 trays 600x400 trayholder (L/R)
390100007	11 trays GN 1/1 rackholder (L/R)
390200004	11 trays GN 1/1 trayholder (L/R)
YSTKIT	Stackable kit
YSTSTK	Stand for stackable column (LxDxH) 850x850x282 mm
YPSTK6040-M	12 trays 600x400 mechanical ventilated proofer (LxDxH) 850x930x740 mm
YPSTK6040-D	12 trays 600x400 digital ventilated proofer (LxDxH) 850x930x740 mm
ON DEMAND	Stainless steel AISI 316 cooking chamber for ego and star 6/7 trays ovens
ON DEMAND	Stainless steel AISI 316 cooking chamber for ego and star 10/11 trays ovens
-	Reversible door opening R/L (optional only at the order placement)
	•

#### **Special** Line

142000002	20 trays GN 1/1 trolley for ego rack
142000001	16 trays 600x400 trolley for ego rack
YSTSLIM	6 levels stand (LxDxH) 513x908x687 mm for ego slim

# **Trays**

### GN 1/1 trays for **Ho.Re.Ca.** Line

220100006	Aluminum not-stick tray for 6 eggs d.53x32,5 cm
220100007	Steel granite enameled tray h.20 GN 1/1
220100009	Pizza tray d.53x32,5 cm
220100014	Aluminum not-stick perforated tray h.20 d. 53x32,5 cm
220100015	Aluminum not-stick tray h.20 d.53x32,5 cm
230100002	Chromed grill rack d.53x32,5 cm
230100005	Roast chicken tray (8 spikes) d.53x32,5 cm
230100006	Grill tray d.53x32,5 cm
220200003	Stainless steel tray h.20 d.53x32,5 cm
220200002	Stainless steel tray h.40 d.53x32,5 cm
220200004	Stainless steel perforated tray h.20 d.53x32,5
220100005	cm Fry steel tray h.40 d.53x32,5 cm

#### 600x400 trays for **Bakery** Line

220100001	Aluminum tray h.20 600x400
220100008	Pizza tray h.20 600x400
220100010	Aluminum perforated tray h.20 600x400
230100001	Grill rack tray 600x400