



C: Steam outlet chimney / Air inlet chimney
V1: Washing solenoid valve
V2: Steam solenoid valve
H: Hood connection
E: Electric connection
S: Drain water
L: Limescale entry

Dimensions and weight

Oven width: 510 mm
Oven depth: 905 mm
Oven height: 850 mm
Net weight full optional: 83 kg

Packaging width: 590 mm
Packaging depth: 980 mm
Packaging height: 1000 mm
Weight with packaging full optional: 95 kg
Packaging volume: 0.58 m³

Installation

Minimum left side distance: 500 mm
Minimum right side distance: 50 mm
Minimum back distance: 50 mm
Min. distance from heat sources: 500 mm

Electrical connection

Supply: 380-415 V 3N 50/60 Hz
230 V 3P 50/60 Hz

Max power: 10.5 kW

Current: 17 A
30 A

Cable dimension: 5x4 mm²
H07RN-F

Water connection

Water wash connection V1: 3/4"
Steam water connection V2: 3/4" softened
Water pressure: 1.5-5 bar
Water hardness: 4° d
Minimum Condutance: 50 µS/cm
Exhaust size S: 32 mm

Capacity

Trays type: 6040
Number of trays: 6
Distance between trays: 70 mm
Max load: 30 kg
Max load single tray: 5 kg

IP rating: IPx4

393900090 DATA_SHEET_SLIM_6T_G19_STEAMER