







C: Steam outlet chimney / Air inlet chimney
V1: Washing solenoid valve
V2: Steam solenoid valve
H: Hood connection
E: Elettric connection
S: Drain water

Dimensions and weight

Oven width: 510 mm
Oven depth: 905 mm
Oven height: 850 mm
Net weight full optional: 79 kg

Packaging width: 590 mm
Packaging depth: 980 mm
Packaging height: 1000 mm
weight with packaging full optional: 91 kg
Packaging volume: 0.58 m³

Installation

Minimum left side distance: 500 mm
Minimum right side distance: 50 mm
Minimum back distance: 50 mm
Min. distance from heat sources: 500 mm

Electrical connection

Supply: 380-415 V 3N 50/60 Hz
230 V 3P 50/60 Hz

Max power: 7.5 kW

Current: 14 A
24 A

Cable: 5x4 mm²
H07RN-F

Water connection

Water wash connection V1:	3/4"
Steam water connection V2:	3/4" softened
Water pressure:	1.5-5 bar
Water hardness:	4° d
Minimun Condutance:	50 µS/cm
Exhaust size S:	32 mm

Capacity

Trays type:	6040
Number of trays:	6
Distance between trays:	70 mm
Max load:	30 kg
Max load single tray:	5 kg

IP rating: IPx4