



- C:** Steam outlet chimney / Air inlet chimney
- V1:** Washing solenoid valve
- V2:** Steam solenoid valve
- H:** Hood connection
- E:** Electric connection
- S:** Drain water
- L:** Limescale entry

Dimensions and weight

Oven width: 510 mm
Oven depth: 905 mm
Oven height: 850 mm
Net weight full optional: 83 kg

Packaging width: 590 mm
Packaging depth: 980 mm
Packaging height: 1000 mm
Weight with packaging full optional: 95 kg
Packaging volume: 0.58 m³

Installation

Minimum left side distance: 500 mm
Minimum right side distance: 50 mm
Minimum back distance: 50 mm
Min. distance from heat sources: 500 mm

Electrical connection

Supply: 380-415 V 3N 50/60 Hz
 230 V 3P 50/60 Hz

Max power: 10.5 kW

Current: 17 A
 30 A

Cable dimension: 5x4 mm²
 H07RN-F

Water connection

Water wash connection V1: 3/4"
Steam water connection V2: 3/4" softened
Water pressure: 1.5-5 bar
Water hardness: 4° d
Minimum Condutance: 50 µS/cm
Exhaust size S: 32 mm

Capacity

Trays type: GN11
Number of trays: 6
Distance between trays: 70 mm
Max load: 30 kg
Max load single tray: 5 kg

IP rating: IPx4