







ego slim

	Pro	Lite
Code model	YLHGN11-06D0WBS003	YLCGN11-06D0WB0003
Capacity	6 trays GN 1/1	6 trays GN 1/1
Pitch	70 mm	70 mm
Dimension mm (LxDxH)	510x905x850	510x905x850
Weight (kg)	83 kg	79 kg
Power	10,5 kW	7,5 kW
Voltage	380-415 V / 3 N	380-415 V / 3 N
IP protection level	IPx 4	IPx 4



Main features (Pro unit)

- $\ensuremath{\mathbbmsssschule}$ Convection, combi and steam cooking with fixed time or core probe function
- □ Temperature settable from 30°C to 280°C
- ACT Technology (Advanced Clima Technology) with energy conservation thanks to the automatic climate regulation**
- □ Manual, programmed or automatic cooking mode
- Pre uploaded YESRECIPES book divided into categories
- MYCOOKBOOK for saving programs into customizable folders
- \blacksquare Manual or automatic pre-heating mode settable up to 300°c
- Dessibility to save up to 10 cooking phases per program
- HOLD function at the end of the cooking
- 10" multilingual Touchscreen display
- Click&Share function to save recipes with your cover images
- USB interface for HACCP data downloading
- □ Integrated WIFI connection configuration
- Alarms display with autodiagnosis system
- Special cycles: Delta T, Time's up for synchronized cookings, Cook&Go for simultaneous cookings, rapid cooking chamber cool-down, regeneration with core probe or fixed-time mode, proofing cycle
- Manual humidity supply function
- FastSteam technology for immediate steam generation
- YesSteam technology for steam generation with high efficiency steamer**

- Programmable FCS technology (Fast Chimney System) for forced extraction of humidity
- Automatic SCS technology (Smart Chimney System) for forced extraction of humidity
- Settable ventilation speeds (7) + pulse speed with automatic inversion of fans rotation
- 304 stainless steel cooking chamber
- Ergonomic and lightweight handle compliant with HACCP standards
- E Frontal structure with screwless system
- \square Integrated humidity collector aisle
- I Multi-point core probe with external link to the cooking chamber included
- Integrated syphon
- Adjustable feet
- Simply-removable tray holder
- Double glass door with high thermic insulation and easy inspection with safety fan stop system when the door is open
- Halogen inner lamps in the cooking chamber
- Retractable shower included**
- Automatic washing system with monocomponent YesClean (4+1 _ cycles)
- Automatic special cycle for limescale removal from the steamer**
 Loading detergent function
- Integrated mono product tank (YesClean)

)		YLHGN11-06D0 WBS001	
31		ДВ: ДГН МВ:	2 2
	Code model Capacity	6	
uipment unit	Pro unit (full optional) Lite unit		
	Classic unit		
	Convection, combi and steam cooking		
ooking type	Convection, combi and steam cooking with fixed time or core probe function Convection, combi and steam cooking with fixed time or core probe function (mono-point core probe optional) Convection, combi and steam cooking with fixed time or core probe function (multi-point core probe optional)	•	
mperature	ACT technology (advanced clima technology) with energy conservation thanks to the automatic climate regulation Temperature settable from 30°c to 280°c	•	
	Manual cooking mode	۲	
ooking mode	Programmed cooking mode	۲	
	Automatic cooking mode Data storage for the saving programs (99)	۲	
	Pre uploaded YESRECIPES book divided into categories	۲	
cipes memory	MYCOOKBOOK for saving programs into customizable folders	۲	
	Rapid display of free and in use positions 5 cooking phases per program		
oking phases	10 cooking phases per program	۲	
- 1	HOLD function at the end of the cooking	۲	
-heating	Manual or automatic pre-heating mode settable up to 280°c Manual or automatic pre-heating mode settable up to 300°c		
	Manual or automatic pre-heating mode settable up to 300°c Manual controls		
en interface	Multi-function digital display		
en interiace	Multi-function digital display with Yesclima function		
	10" multilingual touchscreen display Click&Share function to save recipes with your cover images	•	
ipheral devices	USB interface for data uploading and downloading (HACCP data also)	Õ	
	Configuration for integrated WIFI connection	۲	
difications and	Possibility to modify cooking parameters during the cycle in operation Instant display of set cooking parameters	•	
olay	Instant display of the set-up cooking program	•	
·	Alarms display with autodiagnosis system	۲	
	Delta T special cooking cycle	•	
	Time's Up special cycle for synchronized cookings Cook&Go special cycle for simultaneous cookings	•	
	Rapid cooking chamber cool-down special cycle	۲	
ecial cycles	Regeneration special cycle	۲	
	Proofing special cycle Special cycle time extension at the end of the cooking process	•	
	Rapid cancellation of memorized recipes	•	
	Manual humidity supply function	۲	
midity and am generation	Humidity release from 0% to 100% Fast Steam technology for immediate steam generation		
an generation	YesSteam technology for steam generation with high-efficiency steamer	•	
	Manual system for forced extraction of humidity		
midity extraction	Programmable FCS technology (fast chimney system) for forced extraction of humidity Automatic SCS technology (smart chimney system) for forced extraction of humidity	•	
	Mono-fan heat supply system	•	
at supply	Multi-fan heat supply system		
	Special ventilation SOFT-BAKING Settable ventilation speeds (3) with automatic inversion of fan rotation		
s speed	Settable ventilation speeds (5) with automatic inversion of fan rotation	۲	
	Special ventilation pulse speed with automatic inversion of fan rotation	۲	
	304 stainless steel cooking chamber		
	•	۲	
oking chamber	304 stainless steel molded cooking chamber	۲	
oking chamber	•	•	
oking chamber	304 stainless steel molded cooking chamber 316 stainless steel molded cooking chamber 304 stainless steel control panel structure Frontal structure with screwless system	•	
oking chamber	304 stainless steel molded cooking chamber 316 stainless steel molded cooking chamber 304 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel	•	
oking chamber	304 stainless steel molded cooking chamber 316 stainless steel molded cooking chamber 304 stainless steel control panel structure Frontal structure with screwless system	•	
oking chamber	304 stainless steel molded cooking chamber 316 stainless steel control panel structure 304 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle	•	
-	304 stainless steel molded cooking chamber 316 stainless steel molded cooking chamber 304 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney	•	
-	304 stainless steel molded cooking chamber 316 stainless steel control panel structure 304 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle	•	
-	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Integrated syphon		
-	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Integrated syphon Adjustable feet		
-	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Integrated syphon	• • • • • • • • • • • • • • • • • • •	
-	304 stainless steel molded cooking chamber 316 stainless steel molded cooking chamber 304 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Integrated syphon Adjustable feet Stackable kit configuration Simply removable rack holder		
en structure	304 stainless steel molded cooking chamber 316 stainless steel molded cooking chamber 304 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Stackable feet Stackable kit configuration Simply removable ray holder Ergonomic and lightweight handle compliant with HACCP standards		
en structure	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Integrated syphon Adjustable feet Stackable kit configuration Simply removable ray holder Ergonomic and lightweight handle compliant with HACCP standards Reversible door opening R/L (optional only at the order placement)		
en structure or	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Integrated syphon Adjustable feet Stackable kit configuration Simply removable rack holder Simply removable tray holder Ergonomic and lightweight handle compliant with HACCP standards Reversible door opening R/L (optional only at the order placement) Double glass door of easy inspection with high thermic insulation Halogen inner lamps in the cooking chamber		
en structure or	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Adjustable feet Stackable kit configuration Simply removable rack holder Simply removable tray holded Ergonomic and lightweight handle compliant with HACCP standards Reversible door opening R/L (optional only at the order placement) Double glass door of easy inspection with high thermic insulation Halogen inner lamps in the cooking chamber		
en structure or	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Integrated syphon Adjustable feet Stackable kit configuration Simply removable rack holder Simply removable tray holder Ergonomic and lightweight handle compliant with HACCP standards Reversible door opening R/L (optional only at the order placement) Double glass door of easy inspection with high thermic insulation Halogen inner lamps in the cooking chamber		
en structure or	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Adjustable feet Stackable kit configuration Simply removable rack holder Simply removable rack on opening R/L (optional only at the order placement) Double glass door of easy inspection with high thermic insulation Halogen inner lamps in the cooking chamber Cooling fan for components protection Safety fanstop when the door is open		
oking chamber en structure or hting surity	304 stainless steel molded cooking chamber 316 stainless steel control panel structure Frontal structure with screwless system Simply-removable control panel Simply-approachable right side Simply-approachable motor compartment Integrated humidity collector aisle Double chimney Mono-point core probe with external link to the cooking chamber Multi-point core probe with external link to the cooking chamber Simply removable feet Stackable kit configuration Simply removable ray holder Ergonomic and lightweight handle compliant with HACCP standards Reversible door opening R/L (optional only at the order placement) Double glass door of easy inspection with high thermic insulation Halogen inner lamps in the cooking chamber Manual external shower		

All Line

260700004-V	External shower kit
400100013	YesClean detergent (box with 12 pcs 1Kg each)
400100022	YesCal limescale product for steamer washing (box with 12 pcs 1kg each)
260900001	Cartridge filter mod.XL with connection head
26090001-1	Cartridge filter mod.XL
260900001-3-V	Connection head for cartridge filter mod.XL
YSTW	Stand wheels kit
061200013-V	Multi-point core probe for Ego, Star, Ego Rack and Ego Slim ovens
061200007-V	Single-point core probe for Mood and Taos ovens

Ho.Re.Ca & Arte Bianca Line

Stainless steel AISI 316 cooking chamber for Ego and Star 6/7 trays ovens (lot of 5 pcs.)
Stainless steel AISI 316 cooking chamber for Ego and Star 10/11 trays ovens (lot of 5 pcs.)
6 trays 600x400 rackholder (Rod Frame)
6 trays 600x400 trayholder ("L" plate)
7 trays GN 1/1 rackholder (Rod frame)
7 trays GN 1/1 trayholder ("L" plate)
10 trays 600x400 rackholder (Rod frame)
10 trays 600x400 trayholder ("L" plate)
11 trays GN 1/1 rackholder (Rod frame)
11 trays GN 1/1 trayholder ("L" plate)
Reversible door opening R/L (optional only at the order placement)
6 levels stand (LxDxH) 850x890x720 mm
Stand for stackable column (LxDxH) 850x850x282 mm
Stackable kit
Stackable kit with hood con- nection tubes kit
Hood connection tubes kit (Only)
Condensation hood
Hood (Without condensing kit)
Condensation hood for Slim ovens
12 trays 600x400 digital ventilated proofer (LxDxH) 850x930x740 mm

Special Line

142000013-V	20 trays GN1/1 trolley for Ego Rack
142000015-V	16 trays 600x400 trolley for Ego Rack
YSTSLIM	6 levels stand (LxDxH) 513x908x687 mm for Ego Slim

GN1/1 Trays

220100006	Aluminium not-stick tray for 6 eggs d.53x32,5 (lot of 5 pcs.)
220100007	Steel granite enameled tray h.20 GN 1/1 (lot of 5 pcs.)
220100009	Pizza tray d.53x32,5 cm (lot of 2 pcs.)
220100014	Aluminium non-stick perforated tray h.20 d. 53x32,5 cm (lot of 5 pcs.)
220100015	Aluminium non-stick tray h.20 d.53x32,5 cm (lot of 5 pcs.)
230100002	Chromed grill rack d.53x32,5 cm (lot of 5 pcs.)
230100005	Roast chicken tray (8 spikes) d.53x32,5 cm (lot of 5 pcs.)
230100006	Grill tray d.53x32,5 cm (lot of 5 pcs.)
220200003	Stainless steel tray h.20 d.53x32,5 cm (lot of 5 pcs.)
220200002	Stainless steel tray h.40 d.53x32,5 cm (lot of 3 pcs.)
220200004	Stainless steel perforated tray h.20 d.53x32,5 (lot of 5 pcs.)
220100005	Fry steel tray h.40 d.53x32,5 cm (lot of 2 pcs.)

600x400 Trays

220100001	Aluminium tray h.20 600x400 (lot of 5 pcs.)
220100008	Pizza tray h.20 600x400 (lot of 2 pcs.)
220100010	Aluminium perforated tray h.20 600x400 (lot of 5 pcs.)
230100001	Grill rack tray 600x400 (lot of 5 pcs.)
220100019	Baguette alluminium perforated tray 600x400 (lot of 2 pcs.)

